
Material name : Evaluation data

Customer's product name :

TDK product name : DC-DC converter
CC3-4805SS-E (SIP model)

TDK-Lambda

TDK Corporation
Power Systems Business Group

DWG.No.	TRSC-1588-1
---------	-------------

Issued 2006/12/01

INDEX

1. Load regulation -----	P2~4
2. Line regulation -----	P5
3. Temperature regulation -----	P6
4. Input current(vs. load current) -----	P7
5. Switching frequency(vs. output power)-----	P7
6. Efficiency(vs. load current) -----	P8
7. Efficiency(vs. input voltage) -----	P8
8. Output rise characteristics -----	P9~10
9. Output fall characteristics -----	P11~12
10. Start/stop input voltage characteristics -----	P13
11. Dynamic load response characteristics -----	P13
12. Over current protection characteristics -----	P14
13. Output ripple and noise characteristics -----	P15
14. Output ripple and noise waveform -----	P16
15. Inrush current waveform -----	P16
16. Temperature distribution -----	P17

* The measurement has been done without external output capacitor.
(Except the output ripple noise measurement.)

(Product specification)

Product name	Input voltage(V)	Output voltage(V)	Output current(mA)	The maximum output power(W)	Ambient temperature(°C)
CC3-4805SS-E	36~76	5 ±3%	0~600	3	-40 ~ +85 *2
		6 ±3% *1	0~500		


*1 TRM and -Vout are short-circuited.

*2 At 50°C or more, output power derating is necessary.


Product name or model, title			
DC-DC converter CC3-4805SS-E			
TDK CORPORATION	Name of drawing	Drawing No.	PAGE
	Evaluation data	TRSC-1588-1	1 / 17

1. Load regulation

Condition Ta : -40°C




Condition Ta : -40°C
TRM: Short-circuited to -Vout.




Product name or model, title			
DC-DC converter CC3-4805SS-E			
TDK CORPORATION	Name of drawing	Drawing No.	PAGE
	Evaluation data	TRSC-1588-1	2 / 17

Condition Ta : 25°C




Condition Ta : 25°C
TRM: Short-circuited to -Vout.




Product name or model, title		
DC-DC converter CC3-4805SS-E		
TDK CORPORATION	Name of drawing	Drawing No.
	Evaluation data	TRSC-1588-1
		PAGE
		3 / 17

Condition Ta : 85°C



Condition Ta : 85°C
TRM: Short-circuited to -Vout.




Product name or model, title		
DC-DC converter CC3-4805SS-E		
TDK CORPORATION	Name of drawing	Drawing No.
	Evaluation data	TRSC-1588-1
		PAGE
		4 / 17

2. Line regulation

Condition


I_{out} : 100%



Condition

I_{out} : 100%

TRM: Short-circuited to -V_{out}.



Product name or model, title

DC-DC converter CC3-4805SS-E

TDK CORPORATION

Name of drawing

Drawing No.

PAGE


Evaluation data

TRSC-1588-1


5 / 17

3. Temperature regulation

Condition Iout : 100%



Condition Iout : 100%
TRM: Short-circuited to -Vout.




Product name or model, title			
DC-DC converter CC3-4805SS-E			
TDK CORPORATION	Name of drawing	Drawing No.	PAGE
	Evaluation data	TRSC-1588-1	6 / 17

4. Input current(vs. load current)

Condition

Ta : 25°C


Vout : 5V



5. Switching frequency(vs. output power)

Condition

Ta : 25°C



Product name or model, title

DC-DC converter CC3-4805SS-E

TDK CORPORATION

Name of drawing

Drawing No.

PAGE


Evaluation data

TRSC-1588-1

7 / 17


6. Efficiency(vs. load current)

Condition Ta : 25°C
Vout : 5V



7. Efficiency(vs. input voltage)

Condition Ta : 25°C
Vout : 5V



Product name or model, title			
DC-DC converter CC3-4805SS-E			
TDK CORPORATION	Name of drawing	Drawing No.	PAGE
	Evaluation data	TRSC-1588-1	8 / 17


8. Output rise characteristics

Condition


Vin : 48V

Ta : 25°C

Iout : 0%



Iout : 100%



Product name or model, title

DC-DC converter CC3-4805SS-E

TDK CORPORATION

Name of drawing

Drawing No.

PAGE


Evaluation data

TRSC-1588-1


9/17

Condition Vin : 48V
 Ta : 25°C
 TRM: Short-circuited to -Vout.

Iout : 0%



Iout : 100%



Product name or model, title

DC-DC converter CC3-4805SS-E

TDK CORPORATION

Name of drawing

Drawing No.

PAGE

Evaluation data

TRSC-1588-1

10 / 17


9. Output fall characteristics

Condition


Vin : 48V

Ta : 25°C

Iout : 0%



Iout : 100%



Product name or model, title

DC-DC converter CC3-4805SS-E

TDK CORPORATION

Name of drawing

Drawing No.

PAGE


Evaluation data

TRSC-1588-1


11 / 17

Condition Vin : 48V
 Ta : 25°C
 TRM: Short-circuited to -Vout.

Iout : 0%



Iout : 100%



Product name or model, title

DC-DC converter CC3-4805SS-E

TDK CORPORATION

Name of drawing

Drawing No.

PAGE

Evaluation data

TRSC-1588-1


12 / 17

10. Start/stop input voltage characteristics

Condition

Iout : 100%

Ta : 25°C



11. Dynamic load response characteristics

Condition

Vin : 48V


Vout : 5V

Iout : 0% ~ 100%

Tr=Tf: 100us

f : 100Hz

Ta : 25°C



Product name or model, title

DC-DC converter CC3-4805SS-E

TDK CORPORATION

Name of drawing

Drawing No.

PAGE

Evaluation data


TRSC-1588-1

13 / 17

12. Over current protection characteristics


Condition

Ta : 25°C



Condition

Vin : 48V



Product name or model, title

DC-DC converter CC3-4805SS-E

TDK CORPORATION

Name of drawing

Evaluation data

Drawing No.

TRSC-1588-1


PAGE

14 / 17

13. Output ripple and noise characteristics

Condition


Iout : 100%



Condition

Iout : 100%

TRM: Short-circuited to -Vout.



Product name or model, title

DC-DC converter CC3-4805SS-E

TDK CORPORATION

Name of drawing

Drawing No.

PAGE


Evaluation data

TRSC-1588-1


15 / 17

14. Output ripple and noise waveform

Condition V_{in} : 48V
 I_{out} : 100%
 T_a : 25°C




(Measurement circuit)



15. Inrush current waveform

Condition V_{in} : 76V
 I_{out} : 100%
 T_a : 25°C



Product name or model, title

DC-DC converter CC3-4805SS-E

TDK CORPORATION

Name of drawing

Drawing No.

PAGE

Evaluation data

TRSC-1588-1


16 / 17

16. Temperature distribution


(Thermography)

Condition
 Vin : 48V
 Vout : 5V
 Iout : 100%
 Ta : 25°C
 Wind velocity : 0m/s

A side(transformer mounting side)



B side



(Main parts)

rise of temperature(ΔT)		
Main swtch(°C)	Rectifier diode(°C)	Transformer(°C)
30.8	43.0	35.1

* We measured the temperatures of parts without the case by using the thermography. Therefore, it might be different a little from the actual temperature.

	Product name or model, title		
	DC-DC converter CC3-4805SS-E		
TDK CORPORATION	Name of drawing	Drawing No.	PAGE
	Evaluation data	TRSC-1588-1	17 / 17